


## Tapered Roller Bearings



select	Inquiry	Bearing No.	Boundary dimensions(mm)						Basic load ratings(KN)		Weight(kg)
			d	D	T	B	C	rsmin	Cr	Cor	
30203	17	40	13.25	12	11	1	20.5	20.3	0.08		
30204	20	47	15.25	14	12	1	28.2	28.7	0.127		
30205	25	52	16.25	15	13	1	31.5	34	0.154		
30206	30	62	17.25	16	14	1	43.5	48	0.241		
30207	35	72	18.25	17	15	1.5	55.5	61.5	0.344		
30208	40	80	19.75	18	16	1.5	61	67	0.435		
30209	45	85	20.75	19	16	1.5	67.5	78.5	0.495		
30210	50	90	21.75	20	17	1.5	77	93	0.563		
30211	55	100	22.75	21	18	2	93	111	0.74		
30212	60	110	23.75	22	19	2	105	125	0.949		
30213	65	120	24.75	23	20	2	123	148	1.18		
30214	70	125	26.25	24	21	2	131	162	1.26		
30215	75	130	27.25	25	22	2	139	175	1.41		
30216	80	140	28.25	26	22	2.5	160	200	1.72		
30217	85	150	30.5	28	24	2.5	183	232	2.14		
30218	90	160	32.5	30	26	2.5	208	267	2.66		
30219	95	170	34.5	32	27	3	226	290	3.07		
30220	100	180	37	34	29	3	258	335	3.78		
30221	105	190	39	36	30	3	287	380	4.39		
30222	110	200	41	38	32	3	325	435	5.18		

### Tapered Roller Bearings

30224	120	215	43.5	40	34	3	345	470	6.23
30226	130	230	43.75	40	34	4	375	505	7.25
30303	17	47	15.25	14	12	1	28.9	26.3	0.134
30304	20	52	16.25	15	13	1.5	35.5	34	0.16
30305	25	62	18.25	17	15	1.5	48.5	47.5	0.272
30306	30	72	20.75	19	16	1.5	60	61	0.408
30307	35	80	22.75	21	18	2	75	77	0.54
30308	40	90	25.25	23	20	2	91.5	102	0.769
30309	45	100	27.25	25	22	2	111	126	1.01
30310	50	110	29.25	27	23	2.5	133	152	1.31