


## Thrust Ball Bearings



select	Inquiry	Bearing No.	Boundary dimensions(mm)				Basic load ratings(KN)		Weight(kg)
			d	D	T	rsmin	Cr	Cor	
51100	10	24	9	0.3	10	14	0.021		
51101	12	26	9	0.3	10.3	15.4	0.023		
51102	15	28	9	0.3	10.5	16.8	0.024		
51103	17	30	9	0.3	10.8	18.2	0.026		
51104	20	35	10	0.3	14.2	24.7	0.04		
51105	25	42	11	0.6	19.6	37	0.06		
51106	30	47	11	0.6	20.4	42	0.069		
51107	35	52	12	0.6	20.4	44.5	0.085		
51108	40	60	13	0.6	26.9	63	0.125		
51109	45	65	14	0.6	27.9	69	0.148		
51110	50	70	14	0.6	28.8	75.5	0.161		
51111	55	78	16	0.6	35	93	0.226		
51112	60	85	17	1	41.5	113	0.296		
51113	65	90	18	1	41.5	117	0.338		
51114	70	95	18	1	43	127	0.356		
51115	75	100	19	1	44.5	136	0.399		
51116	80	105	19	1	44.5	141	0.422		
51117	85	110	19	1	46	150	0.444		
51118	90	120	22	1	29.5	190	0.687		
51120	100	135	25	1	85	268	0.987		

### Thrust Ball Bearings

51122	110	145	25	1	87	288	1.07
51124	120	155	25	1	89	310	1.11
51126	130	170	30	1	104	350	1.73
51128	140	180	31	1	107	375	1.9
51130	150	190	31	1	109	400	2
51132	160	200	31	1	112	425	2.1
51134	170	215	34	1.1	134	510	2.77
51136	180	225	34	1.1	135	525	2.92
51138	190	240	37	1.1	170	655	3.75
51140	200	250	37	1.1	172	675	3.92