


# SB Series



select	Inquiry	Bearing No.	d		Dimensions [mm]								Basic Load Rating(N)		Weight(kg)
			in	mm	Be	D	Bi	n	m	G	h	ds	Cr	Cor	
SB201		12	12	40	22	6	16	4.5	3.6	M5X0.8	9600	4600	0.1		
SB201-18	1/2	12	12	40	22	6	16	4.5	3.6	M5X0.8	9600	4600	0.1		
SB202		15	12	40	22	6	16	4.5	3.6	M5X0.8	9600	4600	0.09		
SB202-10	5/8	15	12	40	22	6	16	4.5	3.6	M5X0.8	9600	4600	0.09		
SB203		17	12	40	22	6	16	4.5	3.6	M5X0.8	9600	4600	0.08		
SB203-11	11/16	17	12	40	22	6	16	4.5	3.6	M5X0.8	9600	4600	0.08		
SB204-12	3/4	20	14	47	25	7	18	4.5	3.9	M6X1.0	12800	6650	0.12		
SB204		20	14	47	25	7	18	4.5	3.9	M6X1.0	12800	6650	0.12		
SB205-14	7/8	25	15	52	27	7.5	19.5	5.5	3.9	M6X1.0	14000	7880	0.16		
SB205		25	15	52	27	7.5	19.5	5.5	3.9	M6X1.0	14000	7880	0.16		
SB205-16	1	25	15	52	27	7.5	19.5	5.5	3.9	M6X1.0	14000	7880	0.16		
SB206-18	1 1/8	30	16	62	30	8	22	6	5	M6X1.0	19500	11200	0.25		
SB206		30	16	62	30	8	22	6	5	M6X1.0	19500	11200	0.25		
SB206-19	1 3/16	30	16	62	30	8	22	6	5	M6X1.0	19500	11200	0.25		
SB206-20	1 1/4	30	16	62	30	8	22	6	5	M6X1.0	19500	11200	0.25		
SB207-20	1 1/4	35	17	72	32	8.5	23.5	6.5	5.5	M8X1.0	25700	15200	0.36		
SB207-22	1 3/8	35	17	72	32	8.5	23.5	6.5	5.5	M8X1.0	25700	15200	0.36		
SB207		35	17	72	32	8.5	23.5	6.5	5.5	M8X1.0	25700	15200	0.36		
SB207-23	1 7/16	35	17	72	32	8.5	23.5	6.5	5.5	M8X1.0	25700	15200	0.36		

## SB Series

SB208-24	1 1/2	40	18	80	34	9	25	7	6	M8X1. 0	29600	18200	0.45
SB208		40	18	80	34	9	25	7	6	M8X1. 0	29600	18200	0.45
SB209-26	1 5/8	45	19	85	41.2	10.2	31	8.2	6.3	M8X1.0	31850	20800	0.56
SB209-27	$\frac{1}{11/16}$	45	19	85	41.2	10.2	31	8.2	6.3	M8X1.0	31850	20800	0.56
SB209		45	19	85	41.2	10.2	31	8.2	6.3	M8X1.0	31850	20800	0.56
SB209-28	1 3/4	45	19	85	41.2	10.2	31	8.2	6.3	M8X1.0	31850	20800	0.56
SB210-30	1 7/8	50	20	90	43.5	10.9	32.6	9.2	6.5	M8X1.0	35100	23200	0.62
SB210-31	$\frac{1}{15/16}$	50	20	90	43.5	10.9	32.6	9.2	6.5	M8X1.0	35100	23200	0.62
SB210		50	20	90	43.5	10.9	32.6	9.2	6.5	M8X1.0	35100	23200	0.62
SB211-32	2	55	21	100	45.3	11.8	33.5	9.8	7.2	M8X1. 0	43550	29200	1.1
SB211-34	2 1/8	55	21	100	45.3	11.8	33.5	9.8	7.2	M8X1. 0	43550	29200	1.1